

1.27mm CENTRE SPACING FLAT CABLE

9127 – 9128 SERIES. AWG 28 (7 x 36). 1.27mm (0.050").

Features

- Available in 9, 10, 14, 15, 16, 20, 25, 26, 34, 40, 50, 60 and 64 ways
- Conductor stranded. AWG 28 (7 X 36)
- Insulator Material: PVC colour Grey (Mono Colour) and different colours in the multicoloured version (Consult)
- Insulation Resistance: 1 GΩ/m min.
- Dielectric Strength: 2000 VAC/1 Min.
- Impedance: 100Ω
- Flame test: VW-1. UL 2651 (300V, 105°C)
- Optional: AWG 26 (For other options consult the Sales Office)

Dimensional Information

Dimensional Information

Circuit Size	Part Number		Dimensions	
	Mono Coloured	Multicoloured	A	B
09	9127 - 0928	9128 - 0928	11.43 (0.450)	10.16 (0.400)
10	9127 - 1028	9128 - 1028	12.70 (0.500)	11.43 (0.450)
14	9127 - 1428	9128 - 1428	17.78 (0.700)	16.51 (0.650)
15	9127 - 1528	9128 - 1528	19.05 (0.750)	17.78 (0.700)
16	9127 - 1628	9128 - 1628	20.32 (0.800)	19.05 (0.750)
20	9127 - 2028	9128 - 2028	25.40 (1.000)	24.13 (0.950)
25	9127 - 2528	9128 - 2528	31.74 (1.250)	30.47 (1.200)
26	9127 - 2628	9128 - 2628	33.02 (1.300)	31.74 (1.250)
34	9127 - 3428	9128 - 3428	43.18 (1.700)	41.91 (1.650)
40	9127 - 4028	9128 - 4028	50.80 (2.000)	49.53 (1.950)
50	9127 - 5028	9128 - 5028	63.50 (2.500)	62.23 (2.450)
60	9127 - 6028	9128 - 6028	76.20 (3.000)	74.93 (2.950)
64	9127 - 6428	9128 - 6428	81.28 (3.200)	80.01 (3.150)

