

1.00mm HORIZONTAL SMT ZIF CONNECTOR



2130 SERIES. 1.00mm(0.039"). For PCB Solder

Features









- Available in 4 to 32 circuits
- Insulator Material: Glass filled nylon 6T UL 94V-0
- Contact Material: Tin lead plated Phosphor Bronze
- Actuator designed easy for FFC / FPC installation
- With fixed metal tabs to secure connector in place
- Available in Tube or Reel packing

Dimensional Information

Ordering and Dimensional Information

Circuit Size	Part Number		Dimensions		
	Upside contact	Downside cont.	A	B	C
04	2130-2041	2130-2042	3,00(0,118)	11,00(0,433)	5,30(0,209)
05	2130-2051	2130-2052	4,00(0,157)	12,00(0,472)	6,30(0,248)
06	2130-2061	2130-2062	5,00(0,197)	13,00(0,512)	7,30(0,287)
07	2130-2071	2130-2072	6,00(0,236)	14,00(0,551)	8,30(0,327)
08	2130-2081	2130-2082	7,00(0,276)	15,00(0,591)	9,30(0,366)
09	2130-2091	2130-2092	8,00(0,315)	16,00(0,630)	10,30(0,406)
10	2130-2101	2130-2102	9,00(0,354)	17,00(0,669)	11,30(0,445)
11	2130-2111	2130-2112	10,00(0,394)	18,00(0,709)	12,30(0,484)
12	2130-2121	2130-2122	11,00(0,433)	19,00(0,748)	13,30(0,524)
13	2130-2131	2130-2132	12,00(0,472)	20,00(0,787)	14,30(0,563)
14	2130-2141	2130-2142	13,00(0,512)	21,00(0,827)	15,30(0,602)
15	2130-2151	2130-2152	14,00(0,551)	22,00(0,866)	16,30(0,642)
16	2130-2161	2130-2162	15,00(0,591)	23,00(0,906)	17,30(0,681)
17	2130-2171	2130-2172	16,00(0,630)	24,00(0,945)	18,30(0,720)
18	2130-2181	2130-2182	17,00(0,669)	25,00(0,984)	19,30(0,760)
19	2130-2191	2130-2192	18,00(0,709)	26,00(1,024)	20,30(0,799)
20	2130-2201	2130-2202	19,00(0,748)	27,00(1,063)	21,30(0,839)
21	2130-2211	2130-2212	20,00(0,787)	28,00(1,102)	22,30(0,878)
22	2130-2221	2130-2222	21,00(0,827)	29,00(1,142)	23,30(0,917)
23	2130-2231	2130-2232	22,00(0,866)	30,00(1,181)	24,30(0,957)
24	2130-2241	2130-2242	23,00(0,906)	31,00(1,220)	25,30(0,996)
25	2130-2251	2130-2252	24,00(0,945)	32,00(1,260)	26,30(1,035)
26	2130-2261	2130-2262	25,00(0,984)	33,00(1,299)	27,30(1,075)
27	2130-2271	2130-2272	26,00(1,024)	34,00(1,339)	28,30(1,114)
28	2130-2281	2130-2282	27,00(1,063)	35,00(1,378)	29,30(1,154)
29	2130-2291	2130-2292	28,00(1,102)	36,00(1,417)	30,30(1,193)
30	2130-2301	2130-2302	29,00(1,142)	37,00(1,457)	31,30(1,232)
32	2130-2321	2130-2322	30,00(1,181)	38,00(1,496)	32,30(1,271)

Notice: In case of connectors in reel (Automatic mounting), add aN R at the end of code.



1.00mm HORIZONTAL SMT ZIF CONNECTOR






2130 SERIES. For Machine Mounting


Features

- Packing in reel

Circuits of connectors	Dimensions				
	E	F	W1	W2	W3
4 - 9	24.0 (0.945)	-	24.40 (0.961)	30.40 (1.197)	24.40 (0.961)
10 - 15	32.0 (1.260)	28.40 (1.118)	32.40 (1.276)	38.40 (1.512)	32.40 (1.276)
16 - 26	44.0 (1.732)	40.40 (1.596)	44.40 (1.748)	50.40 (1.984)	44.40 (1.748)
27 - 32	56.0 (2.205)	52.40 (2.063)	56.40 (2.220)	62.40 (2.457)	56.40 (2.220)



Width: 32,44,56mm Carrier



Width: 24mm Carrier

