

BOTTOM ENTRY PCB JACK

7613 SERIES For PCB Solder Low Profile PCB Jack


Features

- Available in 4/4, 6/4, 6/6 and 8/8 circuits
- Mates with FCC-68 modular plugs
- Housing Material: Glass filled polyester UL 94V-0
- Contacts: Gold phosphor bronze 0.35mm square
- Gold plating over nickel in Contact Area.
- Tin plating over nickel in Solder Area

Dimensional Information

Ordering and Dimensional Information

Circuit Size	Part Number	Dimensions				
		A	B	C	D	E
4/4	7613 - T441	7.80 (0.307)	11.20 (0.441)	13.30 (0.524)	3.81 (0.150)	11.35 (0.447)
6/4	7613 - T641	10.00 (0.394)	13.20 (0.520)	15.70 (0.619)	6.35 (0.250)	13.35 (0.526)
6/6	7613 - T661	10.00 (0.394)	13.20 (0.520)	15.70 (0.619)	6.35 (0.250)	13.35 (0.526)
8/8	7613 - T881	12.00 (0.472)	15.20 (0.598)	17.50 (0.689)	8.89 (0.350)	15.35 (0.604)



T = Contact Plating

- T = 4. 6μ" gold over 50μ" nickel
- T = 5. 15μ" gold over 50μ" nickel
- T = 6. 30μ" gold over 50μ" nickel
- T = 7. 50μ" gold over 50μ" nickel

