

SIDE ENTRY LOW PROFILE PCB TYPE JACK


7620 SERIES PCB Solder

Features

- Available in 4/4, 6/4, 6/6, 8/8 and 10/10 Circuits
- Housing Material: Glass Filled Polyester UL 94V-0
- Contacts: Gold Phosphor Bronze of 0.35 X 0.45mm
- Low Profile
- Gold Plating over Nickel in Contact Area
- Tin Plating over Nickel in Solder Area
- Mates with FCC-68 Modular Plugs
- Optional: 4/2 and 6/2 Circuits

Dimensional Information

Ordering and Dimensional Information



Circuit Size	Part Number	Dimensions		
		A	B	C
4/4	7620 - T441	11.21 (0.442)	7.62 (0.300)	3.81 (0.150)
6/4	7620 - T641	12.96 (0.511)	10.16 (0.400)	6.35 (0.250)
6/6	7620 - T661	12.96 (0.511)	10.16 (0.400)	6.35 (0.250)
8/8	7620 - T881	15.24 (0.600)	11.43 (0.450)	8.89 (0.350)
10/10	7620 - T101	15.24 (0.600)	11.43 (0.450)	11.43 (0.450)

T = Contact Plating

- T = 4 6μ" Gold over 50μ" Nickel
- T = 5 15μ" Gold over 50μ" Nickel
- T = 6 30μ" Gold over 50μ" Nickel
- T = 7 50μ" Gold over 50μ" Nickel

